

# SAFETY DATA SHEET

DOW AGROSCIENCES LLC

# Product name: N-SERVE™ Nitrogen Stabilizer

Issue Date: 04/27/2015 Print Date: 05/08/2015

DOW AGROSCIENCES LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# **1. IDENTIFICATION**

Product name: N-SERVE™ Nitrogen Stabilizer

Recommended use of the chemical and restrictions on use Identified uses: Stabilizer

# COMPANY IDENTIFICATION

DOW AGROSCIENCES LLC 9330 ZIONSVILLE RD INDIANAPOLIS IN 46268-1053 UNITED STATES

**Customer Information Number:** 

800-992-5994 info@dow.com

# EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 800-992-5994 Local Emergency Contact: 352-323-3500

# 2. HAZARDS IDENTIFICATION

# Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. Flammable liquids - Category 3 Acute toxicity - Category 4 - Oral Skin irritation - Category 2 Skin sensitisation - Sub-category 1B Specific target organ toxicity - single exposure - Category 3 Aspiration hazard - Category 1

Label elements Hazard pictograms



# Signal word: DANGER!

# Hazards

Flammable liquid and vapour. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.

# Precautionary statements

# Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ eye protection/ face protection.

# Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

# Storage

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

# Disposal

Dispose of contents/ container to an approved waste disposal plant.

# Other hazards

no data available

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# Chemical nature: Mixture

This product is a mixture.

Component	CASRN	Concentration
Nitrapyrin	1929-82-4	22.2%
Solvent naphtha (petroleum), light aromatic consists of:	64742-95-6	63.0%
1,2,4-Trimethylbenzene	95-63-6	18.9%
Xylene	1330-20-7	11.4%
1,3,5-Trimethylbenzene	108-67-8	5.0%
Cumene	98-82-8	2.5%

# 4. FIRST AID MEASURES

# Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice. If breathing is difficult, oxygen should be administered by qualified personnel.

**Skin contact:** Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly.

**Eye contact:** Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice.

**Ingestion:** Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

# Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Skin contact may aggravate preexisting dermatitis. Maintain adequate ventilation and oxygenation of the patient. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment.

# 5. FIREFIGHTING MEASURES

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. General purpose synthetic foams (including AFFF type) or protein foams are preferred if available. Alcohol resistant foams (ATC type) may function.

Unsuitable extinguishing media: no data available

# Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Hydrogen chloride. Carbon monoxide. Carbon dioxide.

**Unusual Fire and Explosion Hazards:** Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Dense smoke is produced when product burns.

# Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

**Methods and materials for containment and cleaning up:** Contain spilled material if possible. Pump with explosion-proof equipment. If available, use foam to smother or supress. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact Dow AgroSciences for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

# 7. HANDLING AND STORAGE

**Precautions for safe handling:** Keep out of reach of children. Keep away from heat, sparks and flame. Do not swallow. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor or mist. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Electrically ground and bond all equipment. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

**Conditions for safe storage:** Store in a dry place. Store in original container. Keep container tightly closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies. Minimize sources of ignition, such as static build-up, heat, spark or flame.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Nitrapyrin	ACGIH	TWA	10 mg/m3
	ACGIH	STEL	20 mg/m3
	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable fraction	5 mg/m3
Solvent naphtha (petroleum), light aromatic consists of:	OSHA Z-1	TWA	2,000 mg/m3 500 ppm
-	ACGIH	TWA	200 mg/m3 , as total hydrocarbon vapor

1,2,4-Trimethylbenzene Xylene	ACGIH ACGIH	TWA TWA	25 ppm BEI
	ACGIH	STEL	BEI
	OSHA Z-1	TWA	435 mg/m3 100 ppm
	ACGIH	TWA	100 ppm
	ACGIH	STEL	150 ppm
1,3,5-Trimethylbenzene	ACGIH	TWA	25 ppm
Cumene	ACGIH	TWA	50 ppm
	OSHA Z-1	TWA	245 mg/m3 50 ppm
	OSHA Z-1	TWA	Absorbed via skin
	OSHA P0	TWA	245 mg/m3 50 ppm

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

# Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

# Individual protection measures

**Eye**/face protection: Use safety glasses (with side shields).

# Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Appearance

Physical state Color

Liquid. Colorless to yellow

Odor	Aromatic
Odor Threshold	No test data available
рН	6.26
Melting point/range	Not applicable
Freezing point	No test data available
Boiling point (760 mmHg)	161 °C (322 °F) Literature Approx.
Flash point	closed cup 40 °C (104 °F) ASTM D 56
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No test data available
Upper explosion limit	7.0 % vol Literature
Vapor Pressure	4 mmHg at 20 ℃ (68 °F) Literature Approx.
Relative Vapor Density (air = 1)	3.7 Literature Calculated.
Relative Density (water = 1)	0.98 at 20 ℃ (68 °F) Literature
Water solubility	Literature Immiscible
Partition coefficient: n- octanol/water	no data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	> 3 mPa.s at 20 ℃ (68 °F)
Kinematic Viscosity	No test data available
Explosive properties	No test data available
Oxidizing properties	No test data available
Liquid Density	0.98 g/cm3 at 20 °C (68 °F) Literature
Molecular weight	no data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# **10. STABILITY AND REACTIVITY**

Reactivity: no data available

Chemical stability: Thermally stable at recommended temperatures and pressures.

Possibility of hazardous reactions: Polymerization will not occur.

**Conditions to avoid:** Active ingredient decomposes at elevated temperatures. Generation of gas during decomposition can cause pressure in closed systems. Avoid static discharge.

**Incompatible materials:** Avoid contact with: Acids. Oxidizers. Avoid contact with metals such as: Aluminum alloys. Magnesium. Magnesium alloys.

**Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to:

Carbon monoxide. Carbon dioxide. Hydrogen chloride. Nitrogen oxides. Toxic gases are released during decomposition.

# 11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

# Acute toxicity

#### Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product: LD50, Rat, female, 1,405 mg/kg

# Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: LD50, Rat, male and female, > 5,000 mg/kg

# Acute inhalation toxicity

Prolonged excessive exposure to mist may cause adverse effects. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

As product: LC50, Rat, male and female, 4 Hour, dust/mist, > 6.0 mg/l

# Skin corrosion/irritation

Brief contact may cause moderate skin irritation with local redness. Effects may be slow to heal. May cause drying and flaking of the skin.

# Serious eye damage/eye irritation

May cause slight eye irritation. Corneal injury is unlikely.

# Sensitization

Has demonstrated the potential for contact allergy in mice.

For respiratory sensitization: No relevant data found.

# Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation. May cause drowsiness or dizziness.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the active ingredient(s): In animals, effects have been reported on the following organs: Kidney. Liver. Blood. Female reproductive organs. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use. Based on information for component(s):

In animals, effects have been reported on the following organs: Liver. Respiratory tract. Blood. Kidney. Xylene is reported to have caused hearing loss in laboratory animals upon exposure to high concentrations; such effects have not been reported in humans. Cataracts were observed in rats exposed to cumene vapors.

# Carcinogenicity

For the active ingredient(s): Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans. For the minor component(s) Has caused cancer in laboratory animals. However, the relevance of this to humans is unknown.

# Teratogenicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

For the solvent(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in lab animals only at doses producing severe toxicity in the mother. Exaggerated doses of xylene given orally to pregnant mice resulted in an increase in cleft palate, a common developmental abnormality in mice. In animal inhalation studies, xylene caused toxicity to the fetus but did not cause birth defects.

# **Reproductive toxicity**

For the active ingredient(s): In animal studies, did not interfere with reproduction.

For the solvent(s): In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

# **Mutagenicity**

For the active ingredient(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

# Aspiration Hazard

May be fatal if swallowed and enters airways.

Carcinogenicity		
Component	List	Classification
Solvent naphtha (petroleum),	ACGIH	A3: Confirmed animal carcinogen with
light aromatic consists of:		unknown relevance to humans.
Cumene	IARC	Group 2B: Possibly carcinogenic to
		humans

# **12. ECOLOGICAL INFORMATION**

Ecotoxicological information on this product or its components appear in this section when such data is available.

# Toxicity

# <u>Nitrapyrin</u>

# Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 Hour, 3.4 - 7.9 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Rainbow trout (Oncorhynchus mykiss), static test, 96 Hour, 4 mg/l

# Acute toxicity to aquatic invertebrates

EC50, eastern oyster (Crassostrea virginica), flow-through test, 96 Hour, 1.8 mg/l LC50, Daphnia magna (Water flea), flow-through test, 48 Hour, 2.2 mg/l

# Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 1.7 mg/l

# Chronic toxicity to fish

NOEC, Fathead minnow (Pimephales promelas), 34 d, 2.87 mg/l

# **Toxicity to Above Ground Organisms**

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg). Material is slightly toxic to birds on a dietary basis (LC50 between 1001 and 5000 ppm). oral LD50, Anas platyrhynchos (Mallard duck), 2708mg/kg bodyweight. dietary LC50, Anas platyrhynchos (Mallard duck), 1466mg/kg diet. dietary LC50, Coturnix japonica (Japanese quail), 820mg/kg diet.

# Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 15 d, survival, 209 mg/kg

# Solvent naphtha (petroleum), light aromatic consists of:

# Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 9.22 mg/l, OECD Test Guideline 203 or Equivalent

# **Toxicity to Above Ground Organisms**

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg). Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm). dietary LC50, Colinus virginianus (Bobwhite quail), 8 d, > 6500mg/kg diet. oral LD50, Colinus virginianus (Bobwhite quail), 21 d, > 2150mg/kg bodyweight.

# 1,2,4-Trimethylbenzene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested). LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 7.7 mg/l

# Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 3.6 mg/l

# <u>Xylene</u>

# Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2.6 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

IC50, Daphnia magna (Water flea), 24 Hour, 1 - 4.7 mg/l, OECD Test Guideline 202 or Equivalent

# Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (algae), Static, 73 Hour, Growth rate, 4.36 mg/l, OECD Test Guideline 201 or Equivalent NOEC, Pseudokirchneriella subcapitata (green algae), 73 Hour, Growth rate, 0.44 mg/l, OECD Test Guideline 201 or Equivalent

#### Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), flow-through, 56 d, mortality, > 1.3 mg/l

#### 1,3,5-Trimethylbenzene

### Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Carassius auratus (goldfish), flow-through test, 96 Hour, 12.5 mg/l, Method Not Specified.

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 6 mg/l, OECD Test Guideline 202 or Equivalent

# Acute toxicity to algae/aquatic plants

EbC50, Desmodesmus subspicatus (green algae), 48 Hour, Biomass, 25 mg/l, OECD Test Guideline 201 or Equivalent

# Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.4 mg/l

# **Cumene**

# Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2.7 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 4.0 mg/l, OECD Test Guideline 202 or Equivalent

# Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Biomass, 2.6 mg/l, OECD Test Guideline 201 or Equivalent

# Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.35 mg/l

# **Toxicity to Above Ground Organisms**

oral LD50, redwing blackbird (Agelaius phoeniceus), > 98 mg/kg

# Persistence and degradability

# **Nitrapyrin**

**Biodegradability:** Chemical degradation (hydrolysis) is expected in the environment within days to weeks. Degradation is expected in the soil environment within days to weeks.

# Theoretical Oxygen Demand: 0.97 mg/mg

# Stability in Water (1/2-life)

Hydrolysis, half-life, 186 Hour, pH 5, Half-life Temperature 25 °C Hydrolysis, half-life, 173 - 233 Hour, pH 7, Half-life Temperature 25 °C Hydrolysis, half-life, 129 Hour, pH 9, Half-life Temperature 25 °C

# Solvent naphtha (petroleum), light aromatic consists of:

**Biodegradability:** For the major component(s): Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%). For some component(s): Biodegradation under aerobic static laboratory conditions is low (BOD20 or BOD28/ThOD between 2.5 and 10%).

# 1,2,4-Trimethylbenzene

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.
10-day Window: Not applicable
Biodegradation: 4 - 18 %
Exposure time: 28 d
Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 3.19 mg/mg

# Photodegradation Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals Atmospheric half-life: 0.641 d Method: Estimated.

# **Xylene**

**Biodegradability:** Material is expected to be readily biodegradable. 10-day Window: Pass **Biodegradation:** > 60 % **Exposure time:** 10 d **Method:** OECD Test Guideline 301F or Equivalent Theoretical Oxygen Demand: 3.17 mg/mg

# **Biological oxygen demand (BOD)**

Incubation	BOD
Time	
5 d	37.000 %
10 d	58.000 %
20 d	72.000 %

# Photodegradation

Test Type: Half-life (indirect photolysis) Sensitizer: OH radicals Atmospheric half-life: 19.7 Hour Method: Estimated.

# 1,3,5-Trimethylbenzene

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.
10-day Window: Not applicable
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301C or Equivalent
10-day Window: Not applicable
Biodegradation: 50 %
Exposure time: 4.4 d
Method: Calculated.

# Theoretical Oxygen Demand: 3.19 mg/mg

# Photodegradation

Test Type: Half-life (indirect photolysis) Sensitizer: OH radicals Atmospheric half-life: 3.7 Hour Method: Estimated.

# Cumene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D or Equivalent

# Theoretical Oxygen Demand: 3.20 mg/mg

# **Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	40.000 %
10 d	62.000 %
20 d	70.000 %

Photodegradation Test Type: Half-life (indirect photolysis) Sensitizer: OH radicals Atmospheric half-life: 1.55 d Method: Estimated.

# **Bioaccumulative potential**

# **Nitrapyrin**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.324 Measured Bioconcentration factor (BCF): < 85 Lepomis macrochirus (Bluegill sunfish) 30 d Measured

# Solvent naphtha (petroleum), light aromatic consists of:

**Bioaccumulation:** For the major component(s): Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). For the minor component(s): Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

# 1,2,4-Trimethylbenzene

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.63 Measured Bioconcentration factor (BCF): 33 - 275 Cyprinus carpio (Carp) 56 d Measured

# **Xylene**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): 3.12 Measured **Bioconcentration factor (BCF):** 25.9 Rainbow trout (Salmo gairdneri) Measured

# 1,3,5-Trimethylbenzene

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). **Partition coefficient: n-octanol/water(log Pow):** 3.42 Measured **Bioconcentration factor (BCF):** 161 Pimephales promelas (fathead minnow) Measured

# Cumene

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient: n-octanol/water(log Pow):** 3.4 - 3.7 Measured **Bioconcentration factor (BCF):** 35.5 Fish. Measured

# Mobility in soil

# Nitrapyrin

Potential for mobility in soil is medium (Koc between 150 and 500). **Partition coefficient(Koc):** 321 Measured

# Solvent naphtha (petroleum), light aromatic consists of:

For the major component(s): Potential for mobility in soil is low (Koc between 500 and 2000).

# 1,2,4-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000). **Partition coefficient(Koc):** 720 Estimated.

# **Xylene**

Potential for mobility in soil is medium (Koc between 150 and 500). **Partition coefficient(Koc):** 443 Estimated.

# 1,3,5-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000). **Partition coefficient(Koc):** 741.65 Estimated.

# <u>Cumene</u>

Potential for mobility in soil is low (Koc between 500 and 2000). **Partition coefficient(Koc):** 800 - 2800 Estimated.

# **13. DISPOSAL CONSIDERATIONS**

**Disposal methods:** If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

# **14. TRANSPORT INFORMATION**

DOT

Proper shipping name	Flammable liquids, n.o.s.(XYLENE RANGE AROMATIC SOLVENT)
UN number	UN 1993
Class	3
Packing group	III
Reportable Quantity	Xylene

# Classification for SEA transport (IMO-IMDG):

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(XYLENE RANGE AROMATIC SOLVENT)
UN number	UN 1993
Class	3
Packing group	III
Marine pollutant	1,2,4-Trimethylbenzene, Nitrapyrin
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

# Classification for AIR transport (IATA/ICAO):

Proper shipping name	Flammable liquid, n.o.s.(XYLENE RANGE AROMATIC SOLVENT)
UN number	UN 1993
Class	3
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# **15. REGULATORY INFORMATION**

# **OSHA Hazard Communication Standard**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard Acute Health Hazard Chronic Health Hazard

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Components	CASRN
Nitrapyrin	1929-82-4
Xylene	1330-20-7
Cumene	98-82-8
1,2,4-Trimethylbenzene	95-63-6

# California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

# Pennsylvania (Worker and Community Right-To-KnowAct): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components	CASRN
Nitrapyrin	1929-82-4
Xylene	1330-20-7
1,2,4-Trimethylbenzene	95-63-6
1,3,5-Trimethylbenzene	108-67-8
Cumene	98-82-8

# Pennsylvania (Worker and Community Right-To-KnowAct): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

# United States TSCA Inventory (TSCA)

This product contains chemical substance(s) exempt from U.S. EPA TSCA Inventory requirements. It is regulated as a pesticide subject to Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) requirements.

# Federal Insecticide, Fungicide and Rodenticide Act

EPA Registration Number: 62719-020

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

# WARNING

Causes skin irritation Harmful if swallowed Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

# **16. OTHER INFORMATION**

# Hazard Rating System

NFPA

Health	Fire	Reactivity
2	2	0

# Revision

Identification Number: 101199396 / A211 / Issue Date: 04/27/2015 / Version: 8.0 DAS Code: XRM-4786

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

# Legend

Absorbed via skin	Absorbed via skin
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
BEI	Biological Exposure Indices
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air
	Contaminants
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

# Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW AGROSCIENCES LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.